

4MP Starlight Camera

Fixed Turret IP Camera



FEATURES

- 4MP (2K) IP PoE Starlight Camera
- Fixed 2.8mm Lens with 1/3" CMOS Sensor
- Built-in Microphone
- Smart IR up to 30m (98ft)
- 105.3° Wide View
- IP67 Weather Resistant
- -30°C ~ 60°C

ANALYTICS

- Motion Detection: Object moving in field of view
- Tampering Alarm: Notices of blocked lens
- Human Body Detection



Motion
Detection



Tampering
Alarm



Human Body
Detection

Optional Junction Box



CY-JBTR-WH / BK
Junction box



CY-WM03-WH / BK
Wall mount bracket



CAMERA	
Sensor	1/3" 4.0 megapixel, progressive scan, CMOS
Minimum Illumination	Colour: 0.005Lux (F1.6, AGC ON) 0 lux with IR on
Day/Night	IR-cut filter with auto switch (ICR)
Shutter	Auto/Manual, 1 ~ 1/100000s
Adjustment angle	Pan: 0° ~ 360° Tilt: 0° ~ 80° Rotate: 0° ~ 360°
WDR	120dB
S/N	>52dB
LENS	
Lens	2.8mm@F1.6
Iris	Fixed
Field of View	(H) 105.3° / (V) 57° / (D) 136.9°
DORI Distance	Detect 63m Observe 25.2m Recognize 12.6m Identify 6.3m
ILLUMINATOR	
IR Range	Up to 30m (98 ft) IR range
Wavelength	850nm
IR On/Off Control	Auto/Manual
VIDEO	
Video Compression	Ultra 265, H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main profile, High profile
Frame Rate	Main Stream: 4MP (2688*1520), Max 25fps; 4MP (2560*1440), Max 25fps; 3MP (2304*1296), Max 30fps; 2MP (1920*1080), Max 30fps; Sub Stream: 720P (1280*720), Max 25fps Third Stream: N/A
Video Bit Rate	128 Kbps~16 Mbps
OSD	Up to 4 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 4 areas
Motion Detection	Up to 4 areas
IMAGE	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/ Auto2
Image Setting	Image rotation, brightness, saturation, contrast, sharpness, gain adjustable by web browser
Digital Noise Reduction	2D/3D DNR
Smart IR	Support
Flip	Normal / Vertical / Horizontal / 180°
Dewarping	Support
HLC	Support
BLC	Support
Defog	Digital Defog

ANALYTICS	
Basic Analytics	Motion detection, Tampering alarm, Human body detection
Other Functions	Watermark, IP address filtering, access policy, ARP protection, RTSP authentication, user authentication
AUDIO	
Audio Compression	G.711
Sampling Rate	8KHZ
STORAGE	
Edge Storage	Micro SD, up to 128GB
Network Storage	ANR
NETWORK	
Protocols	IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS, SSH
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API, SDK
User/Host	Up to 32 users. 2 user levels: administrator, common user, operator
Security	Password protection, Strong password, HTTPS encryption, Export operation logs, Basic and digest authentication for RTSP, Digest authentication for HTTP, TLS 1.2, WSSE and digest authentication for ONVIF
Client	CymCam2 / Guard Station / Star4Live
Web Browser	Plug-in required live view: IE 10 and above, Chrome 45 and above, Firefox 52 and above, Edge 79 and above Plug-in free live view: Chrome 57.0 and above, Firefox 58.0 and above, Edge 16 and above
INTERFACE	
Audio I/O	N/A
Alarm I/O	N/A
Built-in Mic	N/A
Network	1 x RJ45 10M/100M Base-TX Ethernet
GENERAL	
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 3W
Power Interface	Ø 5.5mm coaxial power plug
Dimensions	126mm x 94mm (5" x 3.7") (L x H)
Weight	0.35kg (0.77lb)
Material	Camera: metal / Housing: metal/ Ring: plastic
Working/Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	2KV
Reset Button	N/A
Protection	IP67